

Product Description:

JAC P 655 is a Pure Acrylic Polymer Emulsion specially formulated for high performance exterior and interior coatings with an outstanding UV resistance.

Typical Properties:

Film Properties	: Clear, Hard and Glossy
Appearance	: Bluish Translucent Emulsion
Solid Content %	: 50 ± 1
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: < 500
MFFT (° C)	: ~18
pH	: 7-10
Particle Size (µm)	: 0.204 <
Specific Gravity (g/cm ³)	: 1.05 ±0.01

Application:

JAC P 655 is a medium viscosity Pure Acrylic emulsion polymer, specially designed for high performance interior/exterior architectural paints.

Specific Properties:

- Excellent scrub & water resistance.
- Excellent gloss & adhesion to the substrates.
- High resistance to UV light.
- High durable paint.

Storage Conditions:

- Store in closed drums at temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

Storage Stability:

- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.

