

**Product Description:**

JAC-D 150 is a Vinyl Acetate / Acrylic Copolymer Emulsion designed for interior and exterior architectural paints and wall putties.

**Typical Properties:**

Film Properties	: Clear with excellent water resistance
Appearance	: White Milky Emulsion
Solid Content%	: 50 ± 1
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 15,000-30,000
MFFT (° C)	: ~ 9
PH	: 4.5-5.0
Particle Size (µm)	: 0.25-0.5
Specific Gravity (g/cm <sup>3</sup> )	: 1.05 ± 0.01

**Application:**

JAC-D 150 is an excellent high quality binder suitable for indoor & outdoor architectural paints & construction sealants. It is also used to produce wall putties and economical interior wall paints with good scrub resistance.

**Storage Conditions:**

- Store in closed drums at temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

**Storage Stability:**

- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

**Please note: -**

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.