

JAC- D 160

TECHNICAL DATA SHEET

Product Description:

JAC-D 160 modified Vinyl Acetate / Acrylic Copolymer designed for architectural emulsion paints and wall putties with excellent scrub resistance.

Typical Properties:

Appearance	: Milk White Emulsion
Solid Content%	: 50 ± 1
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 2,000 - 5,000
pH	: 4.5-5.5
Specific Gravity (g/cm ³)	: 1.07 ± 0.01

Applications:

- Interior & Exterior Matt, Semi-Gloss emulsion paints.
- Wall putties & primers

Features :

- Excellent scrub resistance.
- Clear, glossy & flexible film.
- High pigment binding capacity.

Storage & Stability Conditions :

- Store in closed drums at temperature (5- 35 °C), avoid freezing temperatures & direct heat.
- Stable for 12 months at appropriate storage conditions.
- Keep containers sealed to prevent water evaporation and skin forming.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.