

JAC-D 175PLUS

TECHNICAL DATA SHEET

Product Description:

JAC-D 175PLUS is developed Vinyl Acetate / Acrylic Copolymer designed for architectural emulsion paints and wall putties.

Typical Properties:

Appearance : Milk White Emulsion

Film Properties : Clear & Flexible

Solid Content % : 50 ± 1

Viscosity (cps) : 20,000-30,000
Sheen VM1/VM2 @25 (°C)

MFFT (°C) : ~ 9

pH : 4.5-5.0

Specific Gravity (g/cm³) : 1.05 ± 0.01

Applications:

- Specially designed to produce Eggshell, Vinyl Silk and Semi-gloss architectural emulsion paints.
- High quality wall putties.

Storage & Stability Conditions:

- Store in closed drums at temperature (5- 35 °C), avoid freezing temperatures & direct heat.
- Stable for 12 months at appropriate storage conditions.
- Keep containers sealed to prevent water evaporation and skin forming.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.