

## JAC-ST 395 LVH

## TECHNICAL DATA SHEET

### **Product Description:**

JAC-ST 395 LVH is a specially formulated Styrene Acrylic Copolymer Emulsion for specific applications where high elasticity and water barrier properties are required.

### **Typical Properties:**

Film Properties	: Clear, Elastic, and Glossy
Appearance	: Milky White Emulsion
Solid Content %	: $55 \pm 1$
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 300 – 2,000
MFFT	: $< 1$ °C
pH	: 7– 9
Specific Gravity (g/cm <sup>3</sup> )	: $1.03 \pm 0.01$

### **Application:**

1. Waterproof coatings.
2. Cementitious coatings.
3. Roof coatings.
4. Tile adhesive.
5. Excellent bonding to old concrete & masonry surfaces.

### **Storage Conditions:**

- Store in closed drums at temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

### **Storage Stability:**

- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

#### **Please note: -**

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.