

Product Description:

JAC-D 165 is a Vinyl Acetate Acrylic Copolymer emulsion stabilized by anionic/nonionic surfactants and specially formulated to produce emulsion paints with exceptional scrub resistance.

Typical Properties:

Appearance	: Milky Bluish
Solid Content%	: 55 ± 1
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 5,00 – 3,000
MFFT (° C)	: ~ 9
PH	: 4.5-5.0
Specific Gravity (g/cm ³)	: 1.07 ± 0.01

Application:

JAC-D165 can be used in a wide range of high-quality interior emulsion paint formulations including matt, vinyl silk, eggshell, and semi-gloss finishes with exceptional wet scrub resistance. It is also used to produce putties and primers.

Storage Conditions:

- Store in closed drums at temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

Storage Stability:

- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.