

Product Description:

JAC-D 240 Vinyl Acetate/Veova Copolymer Emulsion specially formulated for exterior and interior architectural paints with a high scrub resistance and UV stability.

Typical Properties

Film Properties	: Clear and Glossy
Appearance	: White Milky Emulsion
Solid Content %	: 50 ± 1
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 20,000-35,000
MFFT (° C)	: ~11
pH	: 4.5-5.5
Specific Gravity (g/cm ³)	: 1.06 ± 0.02

Application:

JAC-D 240 Suitable for the production of high quality interior & exterior architectural paints and special decorative putties.

Specific Properties:

JAC-D 240 has high adhesion to the substrates with excellent resistance to scrub, water and UV light.

Storage & Stability Conditions:

- Store in closed drums at temperature (5- 35 °C), avoid freezing temperatures & direct heat.
- Stable for 12 months at appropriate storage conditions.
- Keep containers sealed to prevent water evaporation and skin forming.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.