

JAC- D 475

TECHNICAL DATA SHEET

Product Description:

JAC-D 475 modified Vinyl Acetate/Veova Copolymer Emulsion, formulated for exterior and interior architectural paints with a high scrub resistance and UV stability.

Typical Properties:

Appearance : Milk White Emulsion

Solid Content % : 55 ± 1

Viscosity (cps) : 40,000-60,000
Sheen VM1/VM2 @25 (° C)

MFFT (° C) : ~ 12

pH : 4.5-5.5

Specific Gravity (g/cm³) : 1.06 ± 0.01

Applications:

- Silk, semi-gloss & full glossy paints.
- Special decorative putties.
- Architectural applications.

Features :

- High adhesion to the substrates.
- Very good scrub resistance.
- Clear, glossy & flexible film.

Storage & Stability Conditions:

- Store in closed drums at temperature (5- 35 °C), avoid freezing temperatures & direct heat.
- Stable for 12 months at appropriate storage conditions.
- Keep containers sealed to prevent water evaporation and skin forming.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.