

**JAC- D 52CWR**

**TECHNICAL DATA SHEET**

**Product Description:**

JAC-D 52CWR is Synthetic Emulsion Polymer developed especially as an adhesive for core winding with strong binding; optimal initial wet tack and fast setting.

**Typical Properties:**

Film Properties	: Opaque and Hard
Appearance	: White Milky Emulsion
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 24,000 – 26,000
pH	: 5.5 – 6.5
Specific Gravity (g/cm <sup>3</sup> )	: 1.03 ± 0.01

**Application:**

- JAC- D 52CWR is suitable for core winding with multiple layers.
- Also it's suitable for machines with normal to medium speed.

**Features:**

- Excellent adhesion & very clean running.
- Fast setting & high wet Tack.

**Storage Conditions & Stability:**

- Store in closed drums at temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.
- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

**Please note: -**

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.