

JAC- D 55 CWT

TECHNICAL DATA SHEET

Product Description:

JAC-D 55CWT is Polyvinyl Acetate based Polymer Emulsion developed especially as an adhesive for heavy duty core winding with strong binding; optimal initial wet tack, fast setting and for high-speed machines.

Typical Properties:

Film Properties	: Clear and Flexible
Appearance	: White Milky Emulsion
Viscosity (cps) Sheen VM1/VM2 @25 (° C)	: 3,000 - 4,000
pH	: 4.5 - 5.5
Specific Gravity (g/cm ³)	: 1.04 ± 0.01

Application:

JAC- D 55CWT is suitable for light & heavy-duty core winding applications with the high-speed machine.

Storage Conditions:

- Store in closed drums at temperature (5 - 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

Storage Stability:

- Stable for 12 months at the appropriate storage conditions.
- Avoid frost and direct heat.

Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be an informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee for consequential damages.