





#### JAC-ST 365 LVN

#### **TECHNICAL DATA SHEET**

# **Product Description:**

**JAC–ST 365 LVN** is a general-purpose Styrene Acrylic Copolymer Emulsion with high pigment binding capacity for architectural paints with high PVC, it Includes self-crosslinking system and exhibits outstanding adhesion to concrete surfaces.

### **Typical Properties:**

Film Properties : Clear and Glossy

Appearance : White to off white liquid

Solid Content % :  $50 \pm 1$ 

Viscosity (cps) : 500 - 1,500

Sheen VM1/VM2 @25 (° C)

Glass Transition (° C) : 10

MFFT (°C) : 20

pH : 7.0 - 8.5

Specific Gravity (g/cm<sup>3</sup>) :  $1.00 \pm 0.01$ 

### **Application:**

**JAC–ST 365 LVN** is a general-purpose Styrene Acrylic emulsion copolymer for interior & exterior applications.

It is specially designed for high PVC paints and when high scrub resistance is required. **JAC–ST 365 LVN** is suitable for producing texture coatings, Eggshell to semi-gloss finish, roof coatings and specialty decorative putties.

# **Storage Conditions:**

- Store in closed drums at a temperature (5- 35 °C).
- Keep containers sealed to prevent water evaporation and skin forming.

## **Storage Stability:**

- Stable for 12 months at the appropriate storage conditions.
- Avoid Frost and direct heat.

#### Please note: -

All statements are based on exact investigations in our laboratories and are gained from practical experience. Thus this can only be informal advice. We recommend finding out through your own tests whether the product meets the appropriate requirements. Due to the variety of materials on the market and the different processing methods, which are not influenced by us, we cannot guarantee consequential damages.